

CAS No: MSDS

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
:
Product code : 02523

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Laboratory chemicals, Manufacture of substances

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SPAN LAB
UNIT NO. 14, SKY INDUSTRIAL ESTATE, WALIV, VASAI (E)
401208 Mumbai - INDIA
PH: +91 9820509929
info@spanlab.in www.spanlab.in

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

| | |
|---|------|
| Flammable liquids, Category 3 | H226 |
| Acute toxicity (dermal), Category 4 | H312 |
| Acute toxicity (inhalation:gas) Category 4 | H332 |
| Skin corrosion/irritation, Category 2 | H315 |
| Serious eye damage/eye irritation, Category 2 | H319 |
| Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation | H335 |
| Specific target organ toxicity — Repeated exposure, Category 2 | H373 |
| Aspiration hazard, Category 1 | H304 |

CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of classification categories and H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger

Hazard statements (CLP) : H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H312+H332 - Harmful in contact with skin or if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (CLP) : P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P260 - Do not breathe vapours, fume, gas, dust, spray
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P301+P310 - IF SWALLOWED: immediately call a POISON CENTER or doctor/physician
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P370+P378 - In case of fire: Use ... for extinction

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--------|---|---------|--|
| Xylene | (CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 | 75 - 99 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 STOT SE 3, H335 |
| Phenol | (CAS No) 108-95-2 (EC no) 203-632-7 (EC index no) 604-001-00-2 | 25 - 50 | Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Muta. 2, H341 STOT RE 2, H373 |

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after skin contact : Immediately call a POISON CENTER or doctor/physician. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. Rinse skin with water/shower.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Harmful in contact with skin. Harmful if inhaled. Causes damage to organs.
- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Foam. Dry powder. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. No naked lights. No smoking. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Harmful to aquatic life with long lasting effects.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Collect spillage. On land, sweep or shovel into suitable containers. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe vapours. Use only outdoors or in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container tightly closed. Keep in fireproof place. Keep away from ignition sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

8.2. Exposure controls

| | |
|--------------------------|-------------------------------------|
| Hand protection | : Protective gloves |
| Eye protection | : Chemical goggles or face shield |
| Skin and body protection | : Wear suitable protective clothing |
| Respiratory protection | : Wear respiratory protection |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--------------------------|
| Physical state | : Liquid |
| Colour | : Clear Colorless. |
| Odour | : strong pleasant odour. |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Log Pow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapours.

CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

10.2. Chemical stability

May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Heat. Sparks. Overheating.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Thermal decomposition generates : Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Dermal: Harmful in contact with skin. Inhalation:gas: Harmful if inhaled.

| | |
|------------------|-----------------------|
| ATE CLP (dermal) | 1100 mg/kg bodyweight |
| ATE CLP (gases) | 4500 ppmv/4h |

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Potential adverse human health effects and symptoms : Harmful in contact with skin. Fatal if swallowed. Harmful if inhaled.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to ...

Ecology - waste materials : Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

| | |
|---------------|-----------------|
| UN-No. (ADR) | : 1307 |
| UN-No. (IMDG) | : 1307 |
| UN-No.(IATA) | : 1307 |
| UN-No.(ADN) | : Not regulated |
| UN-No. (RID) | : Not regulated |

14.2. UN proper shipping name

| | |
|---------------------------------------|---------------------------------------|
| Proper Shipping Name (ADR) | : XYLENES |
| Proper Shipping Name (IMDG) | : XYLENES |
| Proper Shipping Name (IATA) | : XYLENES |
| Proper Shipping Name (ADN) | : Not regulated |
| Proper Shipping Name (RID) | : Not regulated |
| Transport document description (ADR) | : UN 1307 XYLENES, 3, III, (D/E) |
| Transport document description (IMDG) | : UN 1307 XYLENES, 3, III (23°C c.c.) |
| Transport document description (IATA) | : UN 1307 XYLENES, 3, III |

14.3. Transport hazard class(es)

ADR

| | |
|----------------------------------|-----|
| Transport hazard class(es) (ADR) | : 3 |
| Danger labels (ADR) | : 3 |



CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

IMDG

Transport hazard class(es) (IMDG) : 3

Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : Not regulated

RID

Transport hazard class(es) (RID) : Not regulated

14.4. Packaging

Packing group (ADR) : III

Packing group (IMDG) : III

Packing group (IATA) : III

Packing group (ADN) : Not regulated

Packing group (RID) : Not regulated

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1

Limited quantities (ADR) : 5L

Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T2

Portable tank and bulk container special provisions (ADR) : TP1

Tank code (ADR) : LGBF

Vehicle for tank carriage : FL

Transport category (ADR) : 3

Special provisions for carriage - Packages (ADR) : V12

CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

Special provisions for carriage - Operation (ADR) : S2

Hazard identification number (Kemler No.) : 30

Orange plates :



Tunnel restriction code (ADR) : D/E

EAC code : 3YE

- Transport by sea

Special provision (IMDG) : 223

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T2

Tank special provisions (IMDG) : TP1

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-D

Stowage category (IMDG) : A

Flash point (IMDG) : 23°C to 30°C c.c.

MFAG-No : 130

- Air transport

PCA Excepted quantities (IATA) : E1

PCA Limited quantities (IATA) : Y344

PCA limited quantity max net quantity (IATA) : 10L

PCA packing instructions (IATA) : 355

PCA max net quantity (IATA) : 60L

CAO packing instructions (IATA) : 366

CAO max net quantity (IATA) : 220L

Special provision (IATA) : A3

ERG code (IATA) : 3L

- Inland waterway transport

Not regulated

- Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions

Contains no REACH candidate substance

Contains no REACH Annex XIV substances.

CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

15.1.2. National regulations

Germany

AwSV/VwVwS Annex reference : Water hazard class (WGK) 2, hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-phrases:

| | |
|-------------------------------|--|
| Acute Tox. 3 (Dermal) | Acute toxicity (dermal), Category 3 |
| Acute Tox. 3 (Inhalation) | Acute toxicity (inhal.), Category 3 |
| Acute Tox. 3 (Oral) | Acute toxicity (oral), Category 3 |
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Acute Tox. 4 (Inhalation:gas) | Acute toxicity (inhalation:gas) Category 4 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment — Chronic Hazard, Category 3 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Muta. 2 | Germ cell mutagenicity, Category 2 |
| Skin Corr. 1B | Skin corrosion/irritation, Category 1B |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT RE 2 | Specific target organ toxicity — Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation |
| H226 | Flammable liquid and vapour |
| H301 | Toxic if swallowed |
| H304 | May be fatal if swallowed and enters airways |
| H311 | Toxic in contact with skin |
| H312 | Harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |

CARBOL XYLENE FOR MICROSCOPY

Safety Data Sheet

| | |
|------|---|
| H319 | Causes serious eye irritation |
| H331 | Toxic if inhaled |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H341 | Suspected of causing genetic defects |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H412 | Harmful to aquatic life with long lasting effects |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product