

MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
:
EC index no : 649-263-00-9
EC no : 232-453-7
CAS No : 8032-32-4
Product code : 00245

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Laboratory chemicals, Manufacture of substances

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SPAN LAB
UNIT NO. 14, SKY INDUSTRIAL ESTATE, WALIV, VASAI (E)
401208 Mumbai - INDIA
PH: +91 9820509929
info@spanlab.in www.spanlab.in

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, H225
Category 2
Skin corrosion/irritation, H315
Category 2
Reproductive toxicity, H361
Category 2
Specific target organ toxicity — Single exposure, Category 3, H336
Narcosis
Specific target organ toxicity — Repeated exposure, Category 2 H373
Aspiration hazard, H304
Category 1
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet

Full text of classification categories and H statements : see section 16

Classification according to Directive 67/548/EEC or 1999/45/EC

F; N; Xn; Carc.Cat.2; Muta.Cat.2; R11-38-48/20-51/53-62-65-67

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

GHS09

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P273 - Avoid release to the environment

P301+P310 - IF SWALLOWED: Immediately call a doctor

P331 - Do NOT induce vomiting

P261 - Avoid breathing vapours, dust, fume, gas

P280 - Wear protective clothing, protective gloves, face protection, eye protection

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Name : PETROLEUM ETHER 40-60°C Extra Pure
CAS No : 8032-32-4
EC no : 232-453-7
EC index no : 649-263-00-9

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet

Full text of R- and H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash with plenty of soap and water. Wash contaminated clothing before reuse. Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Immediately call a POISON CENTER or doctor/physician. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: May cause genetic defects. May cause cancer. Causes damage to organs.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Foam. Water spray.
Unsuitable extinguishing media	: Do not use extinguishing media containing water.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
--------------------------------	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Use personal protective equipment as required.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: On land, sweep or shovel into suitable containers. Collect spillage.
-------------------------	--

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Do not breathe vapours. Use only outdoors or in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.

Storage conditions : Keep in fireproof place. Keep container tightly closed.

Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Hand protection : Protective gloves

Eye protection : Chemical goggles or safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : Wear respiratory protection

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Clear colourless.

Odour : gasoline or kerosene.

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : 10

Melting point : < -73 °C

Freezing point : No data available

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet

Boiling point	: 40 - 60 °C
Flash point	: -40 °C
Auto-ignition temperature	: 288 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable Highly flammable liquid and vapour
Vapour pressure	: 40 mm Hg at 20°C
Relative vapour density at 20 °C	: 2.5
Relative density	: No data available
Density	: 0.60 - 0.75
Solubility	: Water: Insoluble in water
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.011 - 0.059 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Open flame. Heat. Sparks.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

PETROLEUM ETHER 40-60°C Extra Pure (8032-32-4)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose of contents/container to ...
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Hazardous waste due to toxicity.

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 1268
UN-No. (IMDG)	: 1268
UN-No.(IATA)	: 1268
UN-No.(ADN)	: 1268
UN-No. (RID)	: 1268

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IMDG)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IATA)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (ADN)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (RID)	: PETROLEUM DISTILLATES, N.O.S.
Transport document description (ADR)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS
Transport document description (IMDG)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, II, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3



IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3



IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet



ADN

Transport hazard class(es) (ADN) : 3

Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3

Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1

Special provision (ADR) : 640C, 363, 664

Limited quantities (ADR) : 1L

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T7

Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28

Tank code (ADR) : L1.5BN

Vehicle for tank carriage : FL

Transport category (ADR) : 2

Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet

Orange plates



Tunnel restriction code (ADR) : D/E
EAC code : 3YE

- Transport by sea

Special provision (IMDG) : 363
Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP1, TP8, TP28
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : B
MFAG-No : 128

- Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provision (IATA) : A3
ERG code (IATA) : 3H

- Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 363, 640C
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

- Rail transport

Classification code (RID) : F1
Special provision (RID) : 363, 640C
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T7
Portable tank and bulk container special provisions (RID) : TP1, TP8, TP28
Tank codes for RID tanks (RID) : L1.5BN
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet

Hazard identification number (RID) : 33

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

PETROLEUM ETHER 40-60°C Extra Pure is not on the REACH Candidate List

PETROLEUM ETHER 40-60°C Extra Pure is not on the REACH Annex XIV List

15.1.2. National regulations

Germany

AwSV/VwVwS Annex reference : Water hazard class (WGK) 1, slightly hazardous to water (Classification according to VwVwS, Annex 2; WGK No 27)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2

PETROLEUM ETHER 40-60°C Extra Pure

Safety Data Sheet

STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
F	Highly flammable

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product